

Korytowo, stajnia

| Nr | Średnica [mm] | | Długość [m] | Ilość [szt. | Długość łączna wg średnic [m] | | |
|----|----------------------------------|---------|------------------|-----------------|-------------------------------|----------|----------|
| | A-IIIN | A-IIIIN | | | 6 mm | 10 mm | 12 mm |
| | | | | | | | |
| | Lawy fundamentowe | | | | | | |
| 1 | | 12 | 182.00 | 4 | | | 728.00 |
| 2 | 6 | | 0.90 | 550 | 495.00 | | |
| 3 | | 10 | 1.10 | 220 | | 242.00 | |
| | | | | | | | |
| | Stopy fundamentowe | | | | | | |
| 1 | | 12 | 0.90 | 72 | | | 64.80 |
| 2 | | 12 | 1.10 | 36 | | | 39.60 |
| | | | | | | | |
| | Cokoły fundamentowe | | | | | | |
| 1 | | 12 | 1.15 | 20 | | | 23.00 |
| 2 | 6 | | 1.10 | 55 | 60.50 | | |
| 3 | | 12 | 1.65 | 16 | | | 26.40 |
| 4 | 6 | | 1.10 | 64 | 70.40 | | |
| | | | | | | | |
| | Ściany żelbetowe | | | | | | |
| 1 | | 10 | 4.90 | 100 | | 490.00 | |
| 2 | | 10 | 3.30 | 100 | | 330.00 | |
| 3 | 6 | | 14.00 | 30 | 420.00 | | |
| 4 | 6 | | 7.00 | 42 | 294.00 | | |
| | | | | | | | |
| | Strop nad parterem | | | | | | |
| 1 | | 12 | 6.49 | 100 | | | 649.00 |
| 2 | | 12 | 6.85 | 80 | | | 548.00 |
| 3 | | 12 | 8.14 | 160 | | | 1,302.40 |
| 4 | 6 | | 14.00 | 70 | 980.00 | | |
| | | | | | | | |
| | | | | | | | |
| | Wieńce, rys. nr 12K | | | | | | |
| 1 | | 12 | 60.00 | 4 | | | 240.00 |
| 2 | 6 | | 0.80 | 190 | 152.00 | | |
| 3 | | 12 | 40.00 | 4 | | | 160.00 |
| 4 | 6 | | 0.92 | 120 | 110.40 | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | Długość razem [m] | | | | 2,582.30 | 1,062.00 | 3,781.20 |
| | Ciężar 1 mb [kG] | | | | 0.222 | 0.617 | 0.888 |
| | Ciężar łączny wg średnic [kG] | | | | 573.27 | 655.25 | 3,357.71 |
| | Ciężar razem wg klasy stali [kG] | | | | 573.27 | | 4,012.96 |